

**CBB150**



**150 sq.mm Stud Type Power Terminal Blocks**

CBB series Terminal Blocks are preferred for application using wires of large cross section. The Wire is crimped to a ring / fork lug and is screwed on to the flat current bar of the Terminal Block.

**TECHNICAL DATA**

Rated Voltage	1000 V
Rated Current	309 A
Tightening Torque	14 Nm
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Grey
Type of Connection	Stud / Busbar / Bolt
Product Function	Feed Through
Wire Entry Orientation	Side entry
Mounting Possibility	DIN 35/DIN 35-15 Rail
Stud Size	M12
Operated by	Nut Driver / Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

**CONNECTION DATA**

Conductor Cross Section Stranded min.	16 mm <sup>2</sup>
Conductor Cross Section Stranded max.	150 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	8 AWG
Conductor Cross Section AWG/Kcmil max	300 kcmil
Conductor Cross Section Stranded with Ferrule/Lug min	16 mm <sup>2</sup>
Conductor Cross Section Stranded with Ferrule/Lug max	150 mm <sup>2</sup>

**DIMENSIONS**

Height with DIN 35 x 15 mm rail	54.5mm
Height with DIN 35 x 7.5 mm rail	47.3mm
Length	110mm
Width (Thickness)	48mm

**APPROVALS**



**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
CBB150	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Grey colour	10
CBB150BK	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Black colour	10
CBB150BR	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Brown colour	10
CBB150BU	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Blue colour	10


**ORDERING INFORMATION....**

CAT. NO.	DESCRIPTION	STD. PACK
CBB150GN	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Green colour	10
CBB150O	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Orange colour	10
CBB150R	150 sq.mm Feed through Bolt/Nut Type Terminal Block in Red colour	10
CBB150W	150 sq.mm Feed through Bolt/Nut Type Terminal Block in White colour	10
CBB150Y	150 sq.mm Feed through Bolt/Nut Type Terminal Block in yellow colour	10

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	PPCBB1	Partition Plate in Grey colour	50
	CA794/2	Permanent Shorting Link for 2 way shorting	10
	CA794/3	Permanent Shorting Link for 3 way shorting	10
	CA509/K16	Marking Tag Blank suitable for CTS35UNA / CGT35U Terminal Blocks	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CBBPC2/100	Protective cover is available in 100 mm Length	10
	CBBPC2/160	Protective cover is available in 160 mm Length	10
	CBBPC2/200	Protective cover is available in 200 mm Length	10
	CBBPC2/250	Protective cover is available in 250 mm Length	10

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	8 AWG	8 AWG	16 mm <sup>2</sup>
Conductor Cross Section Stranded max.	300 AWG	300 AWG	150 mm <sup>2</sup>
Rated Voltage	600 V	600 V	1000 V
Rated Current	285 A	285 A	309 A
Tightening Torque	127 lb-in	127 lb-in	14 Nm