

**CX10**



**10 sq.mm Spring Clamp Feed Through compact Terminal Blocks**

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.

**TECHNICAL DATA**

Rated Voltage	1000 V
Rated Current	57 A
Housing Material	Polyamide
Comparative Tracking Index	2
Standard Colour	Grey
Type of Connection	Spring Clamp
Product Function	Feed Through
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

**CONNECTION DATA**

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	10 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	6 AWG
Stripping Length	18 mm

**DIMENSIONS**

Height with DIN 35 x 15 mm rail	57 mm
Height with DIN 35 x 7.5 mm rail	49.5 mm
Length	71.7 mm
Width (Thickness)	10 mm

**APPROVALS**



**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
CX10	10 sq.mm Feed Through Spring Clamp Terminal Block in Grey colour	50
CX10BU	10 sq.mm Feed Through Spring Clamp Terminal Block in Blue colour	50
CX10BK	10 sq.mm Feed Through Spring Clamp Terminal Block in Black colour	50
CX10O	10 sq.mm Feed Through Spring Clamp Terminal Block in Orange colour	50
CX10R	10 sq.mm Feed Through Spring Clamp Terminal Block in Red colour	50
CX10Y	10 sq.mm Feed Through Spring Clamp Terminal Block in Yellow colour	50

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50