


**CXK2.5/4**



**2.5 sq.mm Spring Clamp knife disconnecting compact Terminal Blocks**

<span>The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.</span>

**TECHNICAL DATA**

Rated Voltage	1000 V
Rated Current	22 A
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Grey
Type of Connection	Spring Clamp
Product Function	Knife Type Disconnect and Test
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

**CONNECTION DATA**

Conductor Cross Section Stranded min.	2.5 mm <sup>2</sup>
Conductor Cross Section Stranded max.- Output Side	24 AWG
Conductor Cross Section AWG/Kcmil min	12 AWG
2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max	10 mm <sup>2</sup>

**DIMENSIONS**

Height with DIN 32 rail		mm
Height with DIN 35 x 15 mm rail	45.5	mm
Height with DIN 35 x 7.5 mm rail	38	mm
Length	74.7	mm
Width (Thickness)	5	mm

**APPROVALS**



**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
CXK2.5/4	2.5 sq.mm Knife Disconnecting Spring Clamp Terminal Block in Grey colour	50
CXK2.5/4R	2.5 sq.mm Knife Disconnecting Spring Clamp Terminal Block in Red colour	50
CXK2.5/4Y	2.5 sq.mm Knife Disconnecting Spring Clamp Terminal Block in yellow colour	50
CXK2.5/4BU	2.5 sq.mm Knife Disconnecting Spring Clamp Terminal Block in blue colour	50
CXK2.5/4BK	2.5 sq.mm Knife Disconnecting Spring Clamp Terminal Block in black colour	50
CXK2.5/4GN	2.5 sq.mm Knife Disconnecting Spring Clamp Terminal Block in Green colour	50

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50