


**STH4DTFT**



**Stud Type Terminal Block**

These Terminal Blocks are preferred for applications where the connections are subjected to severe vibrations. The wire is crimped to ring /fork type Lug (Ferrule) and is screwed on to flat current bar on the Terminal Block. The fastening nut always remains captive in the hinged plastic carrier. The Hinged Carrier should be lifted to insert the lugs and then snapped back into position. The nut can then be fastened to complete the connection. By the virtue of the hinged design the Terminal Blocks apart from shrouding the live parts, providing IP20 protection, saves considerable time in wiring. STH4DT Disconnect & Test Terminal Block is used for measuring, control and regulatory circuits. They provide a clear functional advantage for devices having utility instruments and associated transformers. Separate testing points facilitate insertion of test probes. Disconnection is achieved by means of slide link operated with a screwdriver.

**TECHNICAL DATA**

Weight	1000 gms
Rated Voltage	1000 V
Rated Current	41 A
Rated Current - Output Side	1.2 A
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Grey
Type of Connection	Stud / Busbar / Bolt
Product Function	Feed Through
Wire Entry Orientation	Side entry
Mounting Possibility	DIN 32/DIN 35/DIN 35-15 Rail
Screw Size	M4
Stud Size	M4
Operated by	Screw Driver
Fuse Fail Indication Voltage	8 KV

**CONNECTION DATA**

Conductor Cross Section Stranded min.	1.5 mm <sup>2</sup>
Conductor Cross Section Stranded max.	6 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	22 AWG
Conductor Cross Section AWG/Kcmil max	8 AWG
2 Conductors with same Cross Section Stranded min	1.5 mm <sup>2</sup>
2 Conductor with same Cross Section Stranded max	4 mm <sup>2</sup>
Conductor Cross Section Solid min	1.5 mm <sup>2</sup>
Conductor Cross Section Solid max	6 mm <sup>2</sup>
Stripping Length	10 mm

**DIMENSIONS**

Height with DIN 32 rail	56.4 mm
Height with DIN 35 x 15 mm rail	59 mm
Height with DIN 35 x 7.5 mm rail	51.5 mm
Length	86.1 mm
Width (Thickness)	11 mm

**APPROVALS**



**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
STH4DTFT	6 Sq.mm Feed through captive nut type Terminal Block in Grey Colour	50
STH4DTFTBU	6 Sq.mm Feed through captive nut type Terminal Block in Blue Colour	50

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

**ACCESSORIES.....**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	EPSTH4DT	End Plate in Grey colour suitable for STH4DT / STH4DTSH Terminal Block	50
	CA514/13-2	Insulated Removable Shorting Link available in 2 Pole	100
	CA514/13-3	Insulated Removable Shorting Link available in 3 Pole	50
	CA514/13-4	Insulated Removable Shorting Link available in 4 Pole	50
	QJ11/2	2 Pole shorting Plug for STH4DT Terminal Block	25
	CA512/13-2	Removable Shorting link available in 2 Pole	100
	CA512/13-3	Removable Shorting link available in 3 Pole	50
	CA512/13-4	Removable Shorting link available in 4 Pole	50
	LCSTH4DT	Lock Out Cap for STH4DT Terminal Block	50
	CA514/14-2	Insulated Ring Type Shorting Link for 2 way Shorting	100
	CA514/14-3	Insulated Ring Type Shorting Link for 3 way Shorting	50
	CA514/14-4	Insulated Ring Type Shorting Link for 4 way Shorting	50

## RATINGS AS PER STANDARDS

STANDARDS	UL 1059	IEC/EN60947-7-1
Approvals	UL	CE
Conductor Cross Section Stranded min.	22 AWG	1.5 mm <sup>2</sup>
Conductor Cross Section Stranded max.	8 AWG	6 mm <sup>2</sup>
Rated Voltage	600 V	1000 V
Rated Current	50 A	41 A
Tightening Torque	14 lb-in	1.2 Nm