


SALT METER

Model : YK-31SA

ISO-9001, CE, IEC1010



FEATURES

- * Separate electrode, easy operation.
- * The portable Salt meter provides fast, accurate readings, with digital readability and the convenience of a remote probe separately.
- * Measuring range : 0 to 10 % salt.
- * Automatic temp. compensation for the probe.
- * Water resistance on the front panel.
- * All function keys are used the rubber button.
- * Data hold.
- * Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.



Lutron

LUTRON ELECTRONIC

The Art of Measurement

SALT METER

Model : YK-31SA

FEATURES
* Separate electrode, easy operation.
* The portable Salt meter provides fast, accurate readings, with digital readability and the convenience of a remote probe separately.
* Measuring range : 0 to 10 % salt (% weight).
* LCD display for low power consumption & clear read-out even in bright ambient light condition.
* Automatic temp. compensation for the probe.
* Water resistance on the front panel.
* All function keys are used the rubber button.
* Data hold.
* Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
* Built-in Low battery indicator.
* Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.

SPECIFICATIONS	
Display	Large LCD display, 21.5 mm digit height. Max. display count no. 1999..
Measurement & Range	0 to 10 % salt (% weight).
Resolution	0.01 % salt.
Accuracy (23 ± 5 °C)	± 0.5 % salt value
Sampling Time	Approx. 0.4 second.
Data Hold	To freeze the measured pH value on the display.
Temperature Compensation	Automatic, 0 to 50 °C (32 to 122 °F).
Operating Temp.	0 to 50 °C (32 to 122 °F).
Operating Humidity	Max. 80% RH.
Power Supply	DC 9V battery (heavy duty type). 006P, MN1604(PP3) or equivalent.
Power Current	Approx. DC 5 mA.
Weight	270 g/0.60 LB (w/battery & electrode).
Dimension	<i>Meter :</i> 200 x 68 x 30 mm (7.9 x 2.7 x 1.2 inch).
	<i>Electrode :</i> Round, 22 mm Dia. x 120 mm length.
Accessories Included	Instruction Manual..... 1 PC. Salt probe..... 1 PC.
Optional Accessories	Hard carrying case, CA-06 Soft Carrying case with sash, CA-05A

* Appearance and specifications listed in this brochure are subject to change without notice.