



VIR-600

VETRIX

INFRARED THERMOMETER

- 12:1 D:S ratio
- Adjustable Emissivity 0.1~1.0
- $\pm 1.5^{\circ}\text{C}$ Temperature Measurement Accuracy
- User Defined Visual And Audio Alarm
- High Contrast EBTN Color Display
- MAX/MIN/AVG/DIFF/Hold modes
- Ring Lasers
- Temperature Recording Up To 99 Groups
- Date/Time Display
- Time Scheduled Measurement



VIR - 600	
Temperature range (°C)	-32°C ~ 600°C
Temperature range (°C)	-25.6°F ~ 1112°F
Accuracy (°C)	±1.5°C or ±1.5%
Accuracy (°C)	±3.0°C or ±1.5%
Repeatability	0.7(°C) or 0.7% (1.5(°F) or 0.7%)
D:S ratio	12:1 (95%)
Response time	≤250ms (95% of reading)
Emissivity	0.1~1.0 (adjustable, stores 5 sets of preset values)
Spectral response	8um~14um
Laser signal	Ring
Laser power	<1mW
Features	
Auto power off	✓
Low battery indication	✓
LCD display	Color EBTN
High/low temperature LED alarm	✓
High/low temperature audible alarm	✓
Data hold	✓
°C/°F selection	✓
MAX/MIN/AVG/DIF mode	✓
Lock measurement	✓
Data storage	99
Scheduled measurement	✓
Backlight	✓
Operating temperature	0°C~50°C (32°F~122°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90% RH (non-condensing)
Tripod mounting hole	✓
Power	
Power	9V battery
Display	30mm x 30mm
Product color	Red and grey
Product net weight	204g
Product size	160mm x 74mm x 48mm
Standard accessories	Battery, carrying bag
Standard individual packing	Gift box, blister, English manual
Standard quantity per carton	20pcs
Standard carton measurement	475mm x 350mm x 250mm
Standard carton gross weight	10.43kg



**No.35, Jalan OP 1/2, Pusat Perdagangan One Puchong, Off Jalan Puchong,
47160 Puchong, Selangor Darul Ehsan, Malaysia.**

T : +603-8071 6322 | F : +603-8071 6822 | E : info@dpstar.com.my