

NTC2K & NTC10K

Temperature probes

SN2BxxPx		Standard Versions	
Sensor type	NTC2K, 2000Ω @ 25°C	SN2B15P1, P2	1.5 m
Range	-40÷120°C	SN2B20P1, P2	2 m
Accuracy	±0.3°C @ 25°C	SN2B25P1, P2	2.5 m
Sheath	∅ 6 x 29 mm; TPE	SN2B30P1, P2, P3	3 m
Cable	2 wires x 0.35 mm ² ; -40÷120°C; TPE; loose leads	SN2B50P1	5 m
Protection	IP67		



SN2B / SN4BxxP1, P2



SN4BxxP2-B

SN4BxxPx		Standard Versions	
Sensor type	NTC10K, 10000Ω @ 25°C	SN4B10P1	1 m
Range	-40÷120°C	SN4B15P1, P2	1.5 m
Accuracy	±0.3°C @ 25°C	SN4B20P1, P2	2 m
Sheath	∅ 6 x 29 mm; TPE	SN4B25P1, P2	2.5 m
Cable	2 wires x 0.35 mm ² ; -40÷120°C; TPE; loose leads	SN4B30P1, P2	3 m
Protection	IP67	SN435P1, P2	3.5 m
		SN4B40P1	4 m
		SN4B50P1, P2	5 m
		SN4B70P1	7 m



SN4BxxP3-Y



SN4BxxP4-S